



MAKING CONNECTIONS


Use only self-locking snap hooks and carabiners with this equipment. Only use connectors that are suitable for each application. Ensure all connections are compatible in size, shape and strength. Do not use equipment that is not compatible. Ensure all connectors are fully closed and locked. Frontline Fall Protection connectors (snap hooks and carabiners) are designed to be used only as specified in each product's user's instructions. See Figure below for illustration of the inappropriate connections stated below. Frontline Fall Protection snap hooks and karabiners should **not be** connected:



To a D-ring to which another connector is attached.



In a manner that would result in a load on the gate.



In a false engagement, where features that protrude from the snap hook or carabiner catch on the anchor and without visual confirmation seems to be fully engaged to the anchor point.



To each other.



Directly to webbing or rope lanyard or tie-back (unless the manufacturer's instructions for both the lanyard and connector specifically allow such a connection)



To any object which is shaped or dimensioned such that the snap hook or karabiner will not close and lock, or that roll-out could occur.



Do not use connector on an anchorage object in the manner depicted in picture-G

Note: Other than 3,600 lbs (16 kN) gated hooks, large throat opening snap hooks should not be connected to standard size D-rings or similar objects which will result in a load on the gate if the hook or D-ring twists or rotates. Large throat snap hooks are designed for use on fixed structural elements such as rebar or cross members that are not shaped in a way that can capture the gate of the hook.